

Linear hose, Braided PU, Ø 6X10 WITH PLASTIC SPRING GUARD - BLUE



AIRSET®

Mod. TL02720610

Linear hose made of braided polyurethane 95 shore, with swiveling fittings, **fitted with plastic spring guard and o-rings (no need for teflon). 16 bar resistant.** To connect pneumatic tools or blow guns to an air compressed system or compressor. Also suitable for fluids like detergents.

All models have ball bearing swivels fitted to allow complete rotation. All linear hoses, are fitted with plastic spring guard: scratchproof, especially on delicate surfaces.

Features

- **Made of enforced polyurethane**
- 16 bar resistant
- UV, oil and abrasion resistant
- **Kink resistant, lays flat and always flexible**
- Enforced: high strength synthetic textile yarn.
- Suitable for hard working conditions
- **Swiveling fittings, male 1/4"**
- **Fittings equipped with o-rings: no need to put teflon on fittings, ready to use with no air leaks!**
- **Fitted with plastic spring guard: scratchproof, especially on delicate surfaces**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

MATERIALS

Hose	Braided Polyurethane (PU)
Spring	Plastic
Fittings	Brass
O-rings	Nbr

TECHNICAL DATA SHEET

Working temperature	-10°/30° - 14/86 °F
Max. Pressure	16 Bar - 232 psi

VERSIONS

Code	Description	Connection	ØHose	Hose length	Colour
TL0272061010	PU Retin linear hose 6x10 - 10 m	Male 1/4"	6x10 mm	10 m - 15 ft	Blue
TL0272061015	PU Retin linear hose 6x10 - 15 m	Male 1/4"	6x10 mm	15 m - 19 ft	Blue
TL0272061020	PU Retin linear hose 6x10 - 20 m	Male 1/4"	6x10 mm	20 m - 30 ft	Blue

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.