

TUCANO BLOW GUN WITH SAFETY PIPE



AIRSET® TUCANO

Cod. TCN H3 4040

Special pipe with side ventilation: prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1). Also, blow gun adopts an angled stainless steel nozzle, designed for professional industrial use. Nozzle construction guarantees resistance to wear; at the same time, stainless steel is resistant to corrosion and chemicals.

Variable airflow trigger

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

Ergonomic handle

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	2,3 N
Air consumption (with a 6bar - 90psi inlet)	275 l/m - 9.7 scfm
Sound level (with a 6bar - 90psi inlet)	80 dB(A)
Connection	1/4" BSP
Weight	136 g - 0.30 lbs
Working temperature	-10°/70° - 14/158 °F
Max. Pressure	16 Bar - 235 psi
Nozzle length	123 mm - 5"

MATERIALS

Handle	Nylon and rubber
Connection	Brass
Valve	Acetal and stainless steel
Body	Nylon
Nozzle	Stainless steel

VERSIONS

Code	Description	Connection
TCN H3 4040	Airset Tucano L130 Osha BSP	1/4" BSP
TCN H3 4041	Airset Tucano L130 Osha NPT	1/4" NPT

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA 1910.95 (b) Max. 90 dB 8h
OSHA STD 1-13.1 Max. 2 bar / 30 psi if the tip becomes blocked

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.