TUCANO L130S - BLOW GUN AND SPIRAL HOSE KIT

AIRSET® TUCANO

Cod. KPPN S340 56

Airset Tucano L130S professional blow gun, with safety nozzle, equipped with spiral hose. Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

Spiral hose features

- Made of polyurethane 95 shore
- Swiveling fittings, male 1/4"
- **Fittings equipped with o-rings**: no need to put teflon on fittings, ready to use with no air leaks!
- Fitted with plastic spring guard: scratchproof, especially on delicate surfaces

Available in different diameter and length
Blow gun features

- Ergonomic grip
- Designed for professional industrial use
- Made of durable materials. Metal parts made of stainless steel, corrosion resistant
- Ergonomic handle: made of soft rubber. Variable airflow trigger for a reduced noise level and increased efficiency
- Solid Brass connection ¼": no air leaks!
- Impact resistant body
- With safety nozzle: Nozzle is silenced for a low noise level. Also, Its rubber tip is designed for delicate surfaces or parts

Kit can be customized to fit customer needs

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

HOSE MATERIALS

Hose	**Polyurethane (PU)**
Spring	**Plastic**
Fittings	**Brass**
O-rings	**Nbr**

BLOW GUN MATERIALS

Handle	**Nylon and rubber**
Thread	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Pipe	**Stainless steel**
Nozzle	**Rubber**

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	**2,5 N**
Air consumption (with a 6bar - 90psi inlet)	**275 l/m - 9.7 scfm**
Sound level (with a 6bar - 90psi inlet)	**83 dB(A)**
Working temperature	**-10°/70° - 14/158 °F**
Max. Pressure	**10 Bar - 145 psi**

VERSIONS

Code	Description	Colour	Connection	øHose	Hose length
KPPN S34056	KIT TUCANO L130 PU 5X8 - 4 m	Black	Male 1/4" BSP	5x8 mm	4 m - 13 ft

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.