

Rubber flow blow gun with air plug



AIRSET™

Code: RUB GM 1010E74

Rubber Flow blow gun with a **an air plug**, already mounted, **European profile DN 7.4**, for connection to a **quick-release coupling**. The Airset Rubber Flow is a blow gun made entirely of **rubber**. It is a **lightweight and compact** tool—**smaller** than the palm of your hand. Thanks to its rubber construction, it's ideal for **blowing on delicate surfaces**.

Features

- **Ultimate Simplicity:** Just bend the barrel of the gun with a finger to blow.
- **Soft Rubber:** **Protects** the most delicate surfaces from scratches and damage.
- **Compactness:** Small dimensions, **perfect to carry in bags, toolboxes, or pockets**.
- **Durability:** Shock-resistant body, ensuring **long life and reliability**.

Maximum Efficiency

The Rubber Flow gun with **quick coupling** ensures an **instant connection** to air compressors thanks to specially designed fittings, allowing operators to **save time** during setup and maximize operational efficiency.

Safety

When using compressed air, **safety** is essential. Ensuring a flawless connection is key to avoiding leaks, which are often found in fittings or couplings. A high-quality connection not only promotes **economic and energy savings** but also a safer working environment. Rubber Flow blow guns with air plug ensure a **reliable seal** and consistent connection, helping make the **workplace safer**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|----------------------------------|--------------------------------|
| Blowing Force (at 6 bar inlet) | 2.5 N |
| Air Consumption (at 6 bar inlet) | 275l/m / 9.7 scfm |
| Noise Level (at 6 bar inlet) | 83 dB(A) |
| Connection | European Profile DN 7.4 |
| Weight | 136 g / 0.30 lbs |
| Working temperature | -10°C/70°C / 14/158 °F |
| Max. Pressure | 10 Bar / 145 psi |

MATERIALS

| | |
|----------|--|
| Air Plug | Steel with Anti-Corrosion Treatment |
| Body | Rubber |

VERSIONS

| Code | Description | Connection |
|----------------|-----------------------|-------------------------|
| RUB GM 1010E74 | Airset Rubber Flow EU | European Profile DN 7.4 |

REGULATIONS

| |
|---------------------------------|
| EU 2003/10/CE Max. 85 dB |
|---------------------------------|

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.