

STANDARD BLOW GUN PRESSURE REDUCER WITH SAFETY PIPE



AIRSET PRESSURE REDUCER

Cod. RSE H310 02

The **safety pipe** with venting technology is the ideal solution for demanding applications, offering the highest level of protection and performance. **Special side openings** ensure **automatic venting** in the event of an outlet obstruction, eliminating any risk of overpressure and accidents.

Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

Two hanging options

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear.

Ergonomic

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

Airset Standard blow guns are tested individually during production: no leaks!

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	1 N
Air consumption (with a 6bar - 90psi inlet)	170 l/m - 6scfm
Sound level (with a 6bar - 90psi inlet)	80 dB(A)
Connection	1/4" BSP
Weight	121 g - 0,26 lbs
Working temperature	-10°/70°
Max. Pressure	6 Bar - 90 psi
Nozzle length	123 mm - 5"

MATERIALS

Handle	Acetal
Connection	Brass
Valve	Acetal and stainless steel
Body	Acetal
Nozzle	Acetal

VERSIONS

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RSE H310 02	Standard Pressure Reducer L130	1/4" BSP	3,5	1 N	170 l/m - 6 scfm	81 dB(A)
RSA H310 03	Standard Pressure Reducer L130 USA	1/4" NPT	2	0,7 N	80 l/m - 2,83 scfm	70 dB(A)

REGULATIONS

OSHA 1910.95 (b) Max. 90 dB 8h

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.