

## Tucano blow gun with flat nozzle and air plug



AIRSET® TUCANO

Cod. TCN PF 4040E74

Tucano Blow Flat blow gun, with a pre-mounted air plug, **European profile DN 7.4**, for connection to a **quick coupling**. Equipped with a **flat nozzle** for a **wide and powerful blow**, but with **low noise level**. Useful in applications where you need to blow away large quantities of chips, debris, or quickly dry **large surfaces**

### Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **fast connection** to air compressors via specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

### Safety

When using compressed air, leaks occur most frequently at fittings or plugs. It is therefore essential to ensure the **quality** of the connection is perfect; this guarantees both **cost and energy savings**. Tucano blow guns with air plug can ensure a durable seal and high-quality connection.

### Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                  |                                |
|----------------------------------|--------------------------------|
| Blowing Force (at 6 bar inlet)   | <b>2.5 N</b>                   |
| Air Consumption (at 6 bar inlet) | <b>275 l/m / 9.5 scfm</b>      |
| Noise Level (at 6 bar inlet)     | <b>80 dB(A)</b>                |
| Connection                       | <b>European Profile DN 7.4</b> |
| Weight                           | <b>136 g / 0.30 lbs</b>        |
| Working temperature              | <b>-10°C/70°C / 14/158 °F</b>  |
| Max. Pressure                    | <b>16 Bar / 235 psi</b>        |
| Nozzle length                    | <b>56 mm / 2"</b>              |

## MATERIALS

|          |                                            |
|----------|--------------------------------------------|
| Handle   | <b>Nylon and Rubber</b>                    |
| Thread   | <b>Brass</b>                               |
| Air Plug | <b>Steel with Anti-Corrosion Treatment</b> |
| Valve    | <b>Acetal and Stainless Steel</b>          |
| Body     | <b>Nylon</b>                               |
| Nozzle   | <b>Nylon</b>                               |

## VERSIONS

| Code            | Description                | Connection              |
|-----------------|----------------------------|-------------------------|
| TCN PF 4040EU74 | Airset Tucano Blow Flat EU | European Profile DN 7.4 |

## REGULATIONS

|                                          |
|------------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB          |
| <b>OSHA</b> Conforme alle normative OSHA |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.