

# Tucano blow gun with safety nozzle and air plug



AIRSET™ TUCANO

Cod. TCN S3 4040E74

Tucano L130 S Blow Gun, with a pre-installed **European profile DN 7.4** quick plug for connection to a **quick-release coupling**. Equipped with a **rubber slotted nozzle** that generates a **wide and effective air jet**. The nozzle is **silenced** for **noise reduction**.

## Speed

The standout feature of the Tucano blow gun with quick coupling is its ability to **connect quickly** to air compressors using specially designed fittings. This coupling allows operators to **easily connect and disconnect the blow gun**, reducing setup times and improving **overall efficiency**.

## Safety

When using compressed air, leaks most often occur at fittings or couplings. It is therefore essential to ensure the **quality** of the connection; this guarantees **cost savings and energy efficiency**. Tucano blow guns with quick coupling ensure a high-quality and long-lasting seal.

## Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with quick coupling; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Quick-coupling blow guns represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.3 N</b>
Air Consumption (at 6 bar inlet)	<b>275 l/m / 9.7 scfm</b>
Noise Level (at 6 bar inlet)	<b>80 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>16 Bar / 235 psi</b>
Nozzle length	<b>162 mm - 6"</b>

**MATERIALS**

Handle	<b>Nylon and Rubber</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Nylon</b>
Nozzle	<b>Rubber</b>
Pipe	<b>Stainless steel</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
TCN S3 4040EU74	Airset Tucano L130 S EU	European Profile DN 7.4

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA</b> Compliant to osha regulation
<b>SUVA PRO</b>

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.