

Tucano blow gun with scratchproof safety nozzle and air plug



AIRSET® TUCANO

Cod. TCN PS 4040E74

Tucano Blow Gun Anti-Scratch with a **air plug**, already assembled, **European profile DN 7.4**, for connection to **quick couplings**. With a **rubber nozzle**, **protects surfaces from scratches**; Its **fan-shaped blow** makes the gun useful for cleaning large surfaces as well as small parts or machinery. Moreover, the nozzle **cannot be blocked** for increased **operator safety**.

Speed

The distinguishing feature of the Tucano blow gun with air plugs is its **quick connection** capability to air compressors through specially designed fittings. This fitting allows operators to **easily connect and disconnect the gun**, reducing setup times and improving overall **operational efficiency**.

Safety

When using compressed air, leaks are more likely to occur at a coupling or fitting. It is therefore essential to ensure the **quality** of the connection is perfect; this ensures both **cost savings and energy savings**. Tucano blow guns with air plugs can guarantee the quality and durability of your connection.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip designed to maximize operator **comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plugs represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.3 N
Air Consumption (at 6 bar inlet)	275 l/m / 7 scfm
Noise Level (at 6 bar inlet)	80dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	16 Bar / 235 psi
Nozzle length	66 mm - 2.6"

MATERIALS

Handle	Nylon and Rubber
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Nylon
Nozzle	Nylon and rubber

VERSIONS

Code	Description	Connection
TCN PS 4040EU74	Airset Tucano Blow Anti-scratch EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation
SUVA PRO

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.