MOUSE BLOW GUN PRESSURE REDUCER WITH SAFETY PIPE



AIRSET™ PRESSURE REDUCER

Cod. RME H310 02

With special **side openings** that ensure **automatic venting** in the event of an outlet obstruction, the **safety pipe** with venting technology offers the highest level of protection and performance for the most demanding applications. **Compliant with OSHA standards** and featuring a bent **stainless steel nozzle** for easy access even in hard-to-reach areas, this robust hose boasts a construction that is resistant to mechanical wear, corrosion and chemicals, **ensuring exceptional durability** even in aggressive environments. Choose the safety pipe with venting technology for complete peace of mind and high performance.

Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

Grip

Blow gun can be operated in vertical, for top air connection. Grip and handle are designed for vertical air supply connection. This offers the best safety and ergonomics for these applications; especially when repetitive use occurs.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	**1 N**
Air consumption (with a 6bar - 90psi inlet)	**170 l/m - 6 scfm**
Sound level (with a 6bar - 90psi inlet)	**81 dB(A)**
Connection	**1/4" BSP**
Weight	**136 g - 0,30 lbs**
Working temperature	**-10°/70°**
Max. Pressure	**6 Bar - 90 psi**
Nozzle length	**123 mm - 5"**

MATERIALS

Handle	**Acetal**
Connection	**Brass**
Valve	**Acetal and stainless steel**
Body	**Acetal**
Nozzle	**Stainless steel**

VERSIONS

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RME H310 02	Mouse Pressure Reducer 130	1/4" BSP	3,5	1 N	170 l/m - 6 scfm	81 dB(A)
RMA H310 07	Mouse Pressure Reducer 130 USA	1/4" NPT	2	0,7 N	80 l/m -2,83 scfm	70 dB(A)

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA 1910.95 (b) Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.