

STANDARD BLOW GUN PRESSURE REDUCER WITH SAFETY NOZZLE



AIRSET PRESSURE REDUCER

Cod. RSE S310 02

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces.

Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

Two hanging options

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear.

Ergonomic

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

Airset Standard blow guns are tested individually during production: no leaks!

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	1 N
Air consumption (with a 6bar - 90psi inlet)	170 l/m - 6 scfm
Sound level (with a 6bar - 90psi inlet)	75 dB(A)
Connection	1/4" BSP
Weight	136 g - 0,30 lbs
Working temperature	-10°/70°
Max. Pressure	6 Bar - 90 psi
Nozzle length	152 mm - 6"

MATERIALS

Handle	Acetal
Connection	Brass
Valve	Acetal and stainless steel
Body	Acetal
Nozzle	Rubber
Pipe	Stainless steel

VERSIONS

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RSE S310 02	Standard Pressure Reducer 130 S	1/4" BSP	3,5	1 N	170 l/m - 6 scfm	75 dB(A)
RSA S310 03	Standard Pressure Reducer 130 S USA	1/4" NPT	2	0,7 N	80 l/m - 2,83 scfm	60 dB(A)

REGULATIONS

OSHA 1910.95 (b) Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

OSHA STD 1-13.1 Max. 2 bar / 30 psi if the tip becomes blocked

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.