TUCANO BLOW GUN PRESSURE REDUCER WITH PLASTIC NOZZLE



Cod. RTE PL40 40

The nozzle creates a concentrated jet of air which reduces turbulence, enabling a more precise, effective blowing force. Nozzle is made of rugged plastic, resistant to wear. Moreover, offers a scratch-free material to minimize the risk on delicate surfaces.

Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

Variable airflow trigger

Tucano adopts a special valve which allows a **progressive control of the lever: this reduces the noise level and air consumption**. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force.

Ergonomic handle

Tucano offers a Soft-Touch handle, **made of soft ergonomic rubber, for comfort and easy handling**. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	**1 N**
Air consumption (with a 6bar - 90psi inlet)	**110 l/m - 3,88 scfm**
Sound level (with a 6bar - 90psi inlet)	**80 dB(A)**
Connection	**1/4" BSP**
Weight	**128 g - 0,28 lbs**
Working temperature	**-10°/70°**
Max. Pressure	**6 Bar - 90 psi**
Nozzle length	**56 mm - 2"**

MATERIALS

Handle	**Nylon and rubber**
Connection	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Nozzle	**Nylon**

VERSIONS

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RTE PL40 40	Tucano Pressure Reducer Blow	1/4" BSP	3,5 bar - 50 psi	1 N	110 l/m - 3,88 scfm	80 dB(A)
RTA PL40 41	Tucano Pressure Reducer Blow USA	1/4" NPT	2 bar - 30 psi	0,6 N	60 l/m - 2,12 scfm	65 dB(A)

REGULATIONS

OSHA 1910.95 (b) Max. 90 dB 8h
EU 2003/10/CE Max. 85 dB
SUVA PRO

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.