

Standard blow gun with angled metal pipe and air plug



AIRSET STANDARD

Code: STD 30 1002E74

Standard L130 blow gun, equipped with a pre-installed **DN 7.4 European air plug** for **quick connection**. Features a bent **stainless steel nozzle**, ideal for harsh environments and extreme conditions.

Features

- **Ergonomic:** The shape of the gun minimizes **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: absolutely **leak-free!**
- Hangable: The blow gun can be **hung in two ways**: resting on the trigger lever or using the **dedicated support**. Both hanging points are reinforced for enhanced wear resistance.
- Time-tested product: This gun has been used by professionals for **over 30 years**—a proven and reliable tool!

Speed

The Standard blow gun with air plug stands out for its ability to **quickly connect** to air compressors thanks to **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup times and **boosting** overall operational efficiency.

Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or couplings. Ensuring **high connection quality** not only promotes **cost savings** but also **energy efficiency**. Standard blow guns with quick couplings **guarantee long-lasting tightness** and **consistent quality** in your **air connection**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.5 N
Air Consumption (at 6 bar inlet)	275 l/m / 9.7 scfm
Noise Level (at 6 bar inlet)	83 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	10 Bar / 145 psi
Nozzle length	123 mm / 5"

MATERIALS

Handle	Acetal
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Acetal
Nozzle	Stainless steel

VERSIONS

Code	Description	Connection
STD 30 1002EU74	Airset Standard L130 EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.