

# STANDARD BLOW GUN WITH SAFETY NOZZLE



AIRSET<sup>®</sup> STANDARD

## Cod. STD S3 1002

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

## Historic Product

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

## Two hanging options

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

## Ergonomic

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

## Airset Standard blow guns are tested individually during production: no leaks!

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Blowing force (with a 6bar - 90psi inlet)   | <b>2,3 N</b>                |
| Air consumption (with a 6bar - 90psi inlet) | <b>275 l/m - 9.7 scfm</b>   |
| Sound level (with a 6bar - 90psi inlet)     | <b>80 dB(A)</b>             |
| Connection                                  | <b>1/4" BSP</b>             |
| Weight                                      | <b>136 g - 0.30 lbs</b>     |
| Working temperature                         | <b>-10°/70° - 14/158 °F</b> |
| Max. Pressure                               | <b>10 Bar - 145 psi</b>     |
| Nozzle length                               | <b>137 mm - 5.40"</b>       |

## MATERIALS

|        |                                   |
|--------|-----------------------------------|
| Handle | <b>Acetal</b>                     |
| Thread | <b>Brass</b>                      |
| Valve  | <b>Acetal and stainless steel</b> |
| Body   | <b>Acetal</b>                     |
| Pipe   | <b>Stainless steel</b>            |
| Nozzle | <b>Rubber</b>                     |

## VERSIONS

| Code        | Description                | Connection |
|-------------|----------------------------|------------|
| STD S3 1002 | Airset Standard L130 S BSP | 1/4" BSP   |
| STD S3 1003 | Airset Standard L130 S NPT | 1/4" NPT   |

## REGULATIONS

|                                                                       |
|-----------------------------------------------------------------------|
| <b>OSHA 1910.95 (b)</b> Max. 90 dB 8h                                 |
| <b>OSHA STD 1-13.1</b> Max. 2 bar / 30 psi if the tip becomes blocked |
| <b>EU 2003/10/CE</b> Max. 85 dB                                       |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.