

Standard L130 - Blow gun, spiral hose, quick coupling and plug kit



AIRSET™

Mod. KPPE 3010E74

Airset Standard L130 blow gun, with bent **metal** tube, complete with **spiral** hose in 95 Shore polyurethane, **safety quick coupling** AT 240 and plug. Suitable for connection with **European profile DN 7.4 quick couplings and plugs**

Ready-to-use kit, with no need to screw the hose onto the compressor system. **The connection** to compressed air **is made via a quick coupling**. It consists of a 95 Shore polyurethane coiled hose assembled with a blow gun with plug, **safety quick coupling** AT240 and plug. **If the system is not equipped with a quick coupling, an additional one can be requested.**

Safety quick coupling

AT 240 has been designed with a **two-stage safety exhaust function**: two movements. Before disconnection, the **pressure is released, eliminating the whiplash effect**, which is harmful to the operator, and **reducing the noise** during disconnection. **This also prevents accidental uncoupling of the coupling.**

Kit features

- Blow gun with bent stainless steel tube, suitable for harsh environments and extreme conditions.
- Spiral hose made of 95 Shore polyurethane; with **plastic anti-kink spring: no scratches** on contact surfaces
- **Safety** quick coupling included. For **quick connection** of the blow gun or to connect other tools
- 2 plugs included: one on the gun to connect to the coupling, the other at the end of the hose to **connect to the system**
- Coiled hose **available in different lengths and diameters**
- Possibility to **customize** the kit with the customer's colors.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

SPIRAL HOSE MATERIALS

Hose	Polyurethane (PU)
Spring	Plastic
Fittings	Brass
O-rings	NBR

BLOW GUN MATERIALS

Trigger	Acetal
Connection bushing	Brass
Valve	Acetal and stainless steel
Body	Acetal
Tube	Stainless steel

QUICK COUPLING MATERIALS

Thread	Brass
Metal parts	Stainless steel
Body	Technopolymer
Seals	NBR

TECHNICAL DATA SHEET

Operating temperature	-10°C / +70°C- 14/158 °F
Maximum inlet pressure	10 bar - 145 psi
Connection	European profile DN 7.4
Blowing force (at 6 bar inlet)	2.5 N
Air consumption (at 6 bar inlet)	275 l/min-9.7 scfm
Sound level (at 6 bar inlet)	83 dB(A)

VERSIONS

Code	Description	Color	Connection	Hose Ø	Hose length
-------------	--------------------	--------------	-------------------	---------------	--------------------

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

KPAE 3010 00E74	Airset Standard L130 Kit 5x8 - 3 m AT240 EU	Blue	European profile DN 7.4	5x8 mm	3 m - 10 ft
KPAE 3010 01E74	Airset Standard L130 Kit 5x8 - 4 m AT240 EU	Blue	European profile DN 7.4	5x8 mm	4 m - 13 ft
KPAE 3010 02E74	Airset Standard L130 Kit 5x8 - 6 m AT240 EU	Blue	European profile DN 7.4	5x8 mm	6 m - 20 ft
KPAE 3010 27E74	Airset Standard L130 Kit 6.5x10 - 6 m AT240 EU	Blue	European profile DN 7.4	6.5x10 mm	6 m - 20 ft
KPAE 3010 28E74	Airset Standard L130 Kit 6.5x10 - 8 m AT240 EU	Blue	European profile DN 7.4	6.5x10 mm	8 m - 26 ft

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.