

Tucano blow gun with safety nozzle and air plug



AIRSET® TUCANO

Cod. TCN S3 4040E74

Tucano L130 S Blow Gun, with a pre-installed **European profile DN 7.4** quick plug for connection to a **quick-release coupling**. Equipped with a **rubber slotted nozzle** that generates a **wide and effective air jet**. The nozzle is **silenced** for **noise reduction**.

Speed

The standout feature of the Tucano blow gun with quick coupling is its ability to **connect quickly** to air compressors using specially designed fittings. This coupling allows operators to **easily connect and disconnect the blow gun**, reducing setup times and improving **overall efficiency**.

Safety

When using compressed air, leaks most often occur at fittings or couplings. It is therefore essential to ensure the **quality** of the connection; this guarantees **cost savings and energy efficiency**. Tucano blow guns with quick coupling ensure a high-quality and long-lasting seal.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with quick coupling; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Quick-coupling blow guns represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.3 N
Air Consumption (at 6 bar inlet)	275 l/m / 9.7 scfm
Noise Level (at 6 bar inlet)	80 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	16 Bar / 235 psi
Nozzle length	162 mm - 6"

MATERIALS

Handle	Nylon and Rubber
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Nylon
Nozzle	Rubber
Pipe	Stainless steel

VERSIONS

Code	Description	Connection
TCN S3 4040EU74	Airset Tucano L130 S EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation
SUVA PRO

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.