Tucano L130 - Blow gun, spiral hose, quick coupling and plug kit



AIRSET®

Code KPAN 3040 56E74

Professional Airset Tucano L130 blow gun, with bent **metal** tube, complete with **spiral** hose in 95 Shore polyurethane, **safety quick coupling** AT 240 and plug. Suitable for connection with **European profile DN 7.4 quick couplings and plugs**

Ready-to-use kit, with no need to screw the hose onto the compressor system. **The connection to compressed air is made via a quick plug**. It consists of a 95 Shore polyurethane coiled hose assembled with a blow gun with plug, **AT240 safety quick coupling** and plug. **If the system is not equipped with a quick coupling, an additional one can be requested**.

Safety quick coupling

AT 240 has been designed with a **two-stage safety exhaust function**: two movements. Before disconnection, the **pressure is released**, **eliminating the whiplash effect**, which is harmful to the operator, and **reducing the noise** during disconnection. **This also prevents accidental uncoupling of the coupling.**

Kit features

- Blow gun with bent stainless steel tube, suitable for harsh environments and extreme conditions.
- Spiral hose made of 95 Shore polyurethane; with **plastic anti-kink spring**: **no scratches** on contact surfaces
- **Safety** quick coupling included. For **quick connection** of the blow gun or to connect other tools
- 2 plugs included: one on the gun to connect to the coupling, the other at the end of the hose to **connect to the system**
- Coiled hose **available in different lengths and diameters**
- Possibility to **customize** the kit with the customer's colors.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

SPIRAL HOSE MATERIALS

Hose	**Polyurethane (PU)**
Spring	**Plastic**
Fittings	**Brass**
O-rings	**NBR**

BLOW GUN MATERIALS

Trigger	**Nylon and rubber**
Connection bushing	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Tube	**Stainless steel**

QUICK COUPLING MATERIALS

Thread	**Brass**
Metal parts	**Stainless steel**
Body	**Technopolymer**
Seals	**NBR**

TECHNICAL DATA SHEET

Operating temperature	**-10°C / +70°C-14/158 °F**
Maximum inlet pressure	**10 bar-145 psi**
Connection	**European profile DN 7.4**
Blowing force (at 6 bar inlet)	**2.5 N**
Air consumption (at 6 bar inlet)	**275 l/min-9.7 scfm**
Sound level (at 6 bar inlet)	**83 dB(A)**

VERSIONS

Code	Description	Color	Connection	Hose Ø	Hose length

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

KPAN 3040 56E74	Airset Tucano L130 Kit 5x8 - 4 m AT240 EU	Black	European profile DN 7.4	5x8 mm	4 m - 13 ft

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.