

Tucano L130S - Blow gun, spiral hose, quick coupling and plug kit



AIRSET™

Code KPAN S340 56E74

Professional Airset Tucano L130 S blow gun with **safety nozzle**, complete with **spiral hose** in 95 Shore polyurethane, **safety quick coupling** AT 240 and plug. Equipped with a **slotted rubber nozzle** that generates a wide and effective air jet. The nozzle is **silenced** to reduce noise; its rubber tip has been developed for sensitive applications where the blown surface **must not be damaged**.

Suitable for connection with **European profile DN 7.4 quick couplings and plugs**

Ready-to-use kit, with no need to screw the hose onto the compressor system. **The compressed air connection is made via a quick coupling**. It consists of a 95 Shore polyurethane spiral hose assembled with a blow gun with plug, **safety quick coupling** AT240 and plug. **If the system is not equipped with a quick coupling, an additional one can be supplied upon request.**

Safety quick coupling

AT 240 has been designed with a **two-stage safety exhaust** function: two movements. Before disconnection, the **pressure is released, eliminating the whiplash effect**, which is harmful to the operator, and **reducing disconnection noise**. **This also prevents accidental disconnection of the coupling.**

Kit features

- Blow gun with bent stainless steel tube, suitable for harsh environments and extreme conditions.
- Spiral hose made of 95 Shore polyurethane, with **plastic anti-kink spring: no scratches** on contact surfaces.
- **Safety** quick coupling included, for **fast connection** of the blow gun or to connect other tools.
- 2 plugs included: one on the gun to connect to the coupling, the other at the end of the hose to **connect to the system**.
- Spiral hose **available in different lengths and diameters**.
- Option to **customize** the kit with the customer's colors.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

SPIRAL HOSE MATERIALS

Hose	Polyurethane (PU)
Spring	Plastic
Fittings	Brass
O-rings	NBR

BLOW GUN MATERIALS

Lever	Nylon and rubber
Connection bushing	Brass
Valve	Acetal and stainless steel
Body	Nylon
Nozzle	Rubber

SAFETY QUICK COUPLING MATERIALS

Thread	Brass
Metal parts	Stainless steel
Body	Technopolymer
Seals	NBR

TECHNICAL DATA SHEET

Operating temperature	-10°/70° - 14/158 °F
Maximum inlet pressure	10 Bar - 145 psi
Connection	European Profile DN 7.4
Blowing force (at 6bar inlet)	2.3 N
Air consumption (at 6bar inlet)	275 l/m - 9.7 scfm
Noise level (at 6bar inlet)	80 dB(A)

VERSIONS

Code	Description	Color	Connection	Hose Ø	Hose length
------	-------------	-------	------------	-----------	----------------

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

KPAN S340 56E74	Airset Tucano L130 S Kit 5x8 - 4 m AT240 EU	Black	European Profile DN 7.4	5x8 mm	4 m - 13 ft
--------------------	--	-------	----------------------------	-----------	-------------

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.