Tucano L130S - Blow gun, spiral hose, quick coupling and plug kit



AIRSET®

Code KPAN S340 56E74

Professional Airset Tucano L130 S blow gun with **safety nozzle**, complete with **spiral hose** in 95 Shore polyurethane, **safety quick coupling** AT 240 and plug. Equipped with a **slotted rubber nozzle** that generates a wide and effective air jet. The nozzle is **silenced** to reduce noise; its rubber tip has been developed for sensitive applications where the blown surface **must not be damaged**.

Suitable for connection with **European profile DN 7.4 quick couplings and plugs**

Ready-to-use kit, with no need to screw the hose onto the compressor system. **The compressed air connection is made via a quick coupling**. It consists of a 95 Shore polyurethane spiral hose assembled with a blow gun with plug, **safety quick coupling** AT240 and plug. **If the system is not equipped with a quick coupling, an additional one can be supplied upon request**.

Safety quick coupling

AT 240 has been designed with a **two-stage safety exhaust** function: two movements. Before disconnection, the **pressure is released**, **eliminating the whiplash effect**, which is harmful to the operator, and **reducing disconnection noise**. **This also prevents accidental disconnection of the coupling.**

Kit features

- Blow gun with bent stainless steel tube, suitable for harsh environments and extreme conditions.
- Spiral hose made of 95 Shore polyurethane, with **plastic anti-kink spring**: **no scratches** on contact surfaces.
- **Safety** quick coupling included, for **fast connection** of the blow gun or to connect other tools.
- 2 plugs included: one on the gun to connect to the coupling, the other at the end of the hose to **connect to the system**.
- Spiral hose **available in different lengths and diameters**.
- Option to **customize** the kit with the customer's colors.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

SPIRAL HOSE MATERIALS

Hose	**Polyurethane (PU)**
Spring	**Plastic**
Fittings	**Brass**
O-rings	**NBR**

BLOW GUN MATERIALS

Lever	**Nylon and rubber**
Connection bushing	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Nozzle	**Rubber**

SAFETY QUICK COUPLING MATERIALS

Thread	**Brass**
Metal parts	**Stainless steel**
Body	**Technopolymer**
Seals	**NBR**

TECHNICAL DATA SHEET

Operating temperature	**-10°/70° - 14/158 °F**
Maximum inlet pressure	**10 Bar - 145 psi**
Connection	**European Profile DN 7.4**
Blowing force (at 6bar inlet)	**2.3 N**
Air consumption (at 6bar inlet)	**275 l/m - 9.7 scfm**
Noise level (at 6bar inlet)	**80 dB(A)**

VERSIONS

Code	Description	Color	Connection	Hose Ø	Hose length

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

KPAN S340 56E74	Airset Tucano L130 S Kit 5x8 - 4 m AT240 EU	Black	European Profile DN 7.4	5x8 mm	4 m - 13 ft

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.