# Standard blow gun with angled metal pipe and air plug



AIRSET STANDARD

**Code: STD 30 1002E74**

Standard L130 blow gun, equipped with a pre-installed **DN 7.4 European air plug** for **quick connection**. Features a bent **stainless steel nozzle**, ideal for harsh environments and extreme conditions.

## Features

- **Ergonomic**: The shape of the gun minimizes **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: absolutely **leak-free!**
- Hangable: The blow gun can be **hung in two ways**: resting on the trigger lever or using the **dedicated support**. Both hanging points are reinforced for enhanced wear resistance.
- Time-tested product: This gun has been used by professionals for **over 30 years**—a proven and reliable tool!

## Speed

The Standard blow gun with air plug stands out for its ability to **quickly connect** to air compressors thanks to **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup times and **boosting** overall operational efficiency.

## Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or couplings. Ensuring **high connection quality** not only promotes **cost savings** but also **energy efficiency**. Standard blow guns with quick couplings **guarantee long-lasting tightness** and **consistent quality** in your **air connection**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing Force (at 6 bar inlet) | **2.5 N** |
| Air Consumption (at 6 bar inlet) | **275 l/m / 9.7 scfm** |
| Noise Level (at 6 bar inlet) | **83 dB(A)** |
| Connection | **European Profile DN 7.4** |
| Weight | **136 g / 0.30 lbs** |
| Working temperature | **-10°C/70°C / 14/158 °F** |
| Max. Pressure | **10 Bar / 145 psi** |
| Nozzle length | **123 mm / 5”** |

MATERIALS

| | |
|---|---|
| Handle | **Acetal** |
| Thread | **Brass** |
| Air Plug | **Steel with Anti-Corrosion Treatment** |
| Valve | **Acetal and Stainless Steel** |
| Body | **Acetal** |
| Nozzle | **Stainless steel** |

VERSIONS

| Code | Description | Connection |
|---|---|---|
| STD 30 1002EU74 | Airset Standard L130 EU | European Profile DN 7.4 |

REGULATIONS

**EU 2003/10/CE** Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.