Standard blow gun with extended metal pipe and air plug



AIRSET STANDARD

Code: STD 35 1002E74

Standard Blow Gun with long barrel and pre-assembled **quick air plug**, **European profile DN 7.4**, for **quick connection**. Equipped with a long tube that allows **better reach** into hard-to-access areas. The extended tube also provides a greater **safety distance** from the surface being blown. The stainless steel tube is suitable for **harsh environments and extreme conditions**.

Features

- **Ergonomic**: The shape of the gun helps to **minimize repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: zero air leaks guaranteed!
- **Hangable**: The gun can be **hung** in two ways—resting on the trigger lever or on the **dedicated hook**. Both supports are reinforced for greater wear resistance.
- **Proven product**: This gun has been around for **30 years**, used by professionals: a tested and reliable product!
- **Three lengths available:**

  STD 35 1002E74 - 327 mm

  STD 52 1002E74 - 497 mm

  STD 10 1002E74 - 1012 mm

Speed

The Standard Blow Gun with quick air plug stands out for its ability to **quickly connect** to air compressors, thanks to the **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup times and **maximizing** overall operational efficiency.

Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or plugs. Ensuring **optimal connection quality** not only promotes **economic** but also **energy savings**. Standard blow guns with quick air plugs **guarantee durable sealing** and **consistent connection quality**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.3 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.7 scfm**
Noise Level (at 6 bar inlet)	**83 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**10 Bar / 145 psi**
Nozzle length	**327 mm / 13”**

MATERIALS

Handle	**Acetal**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Acetal**
Nozzle	**Stainless steel**

VERSIONS

Code	Description	Connection	Pipe lenght
STD 35 1002EU74	Airset Standard L350 EU	European Profile DN 7.4	327 mm - 13"
STD 52 1002EU74	Airset Standard L520 EU	European Profile DN 7.4	497 mm - 20"
STD 10 1002EU74	Airset Standard L1000 EU	European Profile DN 7.4	1012 mm - 40"

REGULATIONS

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.