

STANDARD BLOW GUN WITH EXTENDED SAFETY PIPE



AIRSET[®] STANDARD

Cod. STD H5 1002

Special pipe with side ventilation: prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1). Safety blow gun with an extended pipe for narrow, hard-to-reach spaces. Offers also a better and safety distance from blown surfaces. Pipe is made of stainless steel for professional industrial use. Pipe construction guarantees resistance to a very high mechanical wear; at the same time, stainless steel is resistant to corrosion and chemicals.

Historic Product

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

Two hanging options

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

Ergonomic

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

Airset Standard blow guns are tested individually during production: no leaks!

Built in 1/4" Female brass thread, for a safe connection with no leaks

Available in 3 lengths:

STD H5 1002 - 327 mm / 13"

STD H2 1002 - 497 mm / 20"

STD H0 1002 - 1012 mm / 40"

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	2,3 N
Air consumption (with a 6bar - 90psi inlet)	275 l/m - 9.7 scfm
Sound level (with a 6bar - 90psi inlet)	83 dB(A)
Connection	1/4" BSP
Weight	136 g - 0.30 lbs
Working temperature	-10°/70° - 14/158 °F
Max. Pressure	10 Bar - 145 psi
Nozzle length	327 mm - 13"

MATERIALS

Handle	Acetal
Thread	Brass
Valve	Acetal and stainless steel
Body	Acetal
Nozzle	Stainless steel

VERSIONS

Code	Description	Connection	Pipe lenght
STD H5 1002	Airset STD L350 Osha BSP	1/4" BSP	327 mm
STD H5 1003	Airset STD L350 Osha NPT	1/4" NPT	327 mm
STD H2 1002	Airset STD L520 Osha BSP	1/4" BSP	497 mm
STD H2 1003	Airset STD L520 Osha NPT	1/4" NPT	497 mm
STD H0 1002	Airset STD L1000 Osha BSP	1/4" BSP	1012 mm
STD H0 1003	Airset STD L1000 Osha NPT	1/4" NPT	1012 mm

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA STD 1-13.1 Max. 2 bar / 30 psi if the tip becomes blocked
OSHA 1910.95 (b) Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.