

## Standard blow gun with rubber tip and air plug



AIRSET STANDARD

**Code: STD TP 1002E74**

Standard Tip blow gun with a pre-mounted **DN 7.4 European profile** air plug, for connection to a **quick fitting**. Equipped with a **scratch-resistant rubber** nozzle to minimize the risk of damage to **sensitive surfaces** during use. The “cap-shaped” nozzle design allows for **pressurizing** pipe or mold holes, increasing **cleaning effectiveness**.

### Features

- **Ergonomic:** The shape of the gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: no air leaks!
- Can be hung: The gun can be **hung** in two ways—resting on the trigger lever or on the **dedicated support hook**. Both supports are reinforced for increased wear resistance.
- Proven product: This gun has been in use for **30 years**, trusted by professionals—a reliable and safe product!

### Speed

The Standard blow gun with quick coupling stands out for its **quick connection** capability to air compressors thanks to **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup time and **enhancing** overall operational efficiency.

### Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or couplings. **Ensuring high-quality** connections promotes both **cost** and

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.1 N</b>
Air Consumption (at 6 bar inlet)	<b>200 l/m / 7 scfm</b>
Noise Level (at 6 bar inlet)	<b>83 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>10 Bar / 145 psi</b>
Nozzle length	<b>19 mm / 0.70"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Acetal</b>
Nozzle	<b>Rubber</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD TP 1002EU74	Airset Standard Tip EU	European Profile DN 7.4

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
---------------------------------

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.