Standard blow gun with rubber tip and air plug



AIRSET STANDARD

Code: STD TP 1002E74

Standard Tip blow gun with a pre-mounted **DN 7.4 European profile** air plug, for connection to a **quick fitting**. Equipped with a **scratch-resistant rubber** nozzle to minimize the risk of damage to **sensitive surfaces** during use. The “cap-shaped” nozzle design allows for **pressurizing** pipe or mold holes, increasing **cleaning effectiveness**.

Features

- **Ergonomic**: The shape of the gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: no air leaks!
- Can be hung: The gun can be **hung** in two ways—resting on the trigger lever or on the **dedicated support hook**. Both supports are reinforced for increased wear resistance.
- Proven product: This gun has been in use for **30 years**, trusted by professionals—a reliable and safe product!

Speed

The Standard blow gun with quick coupling stands out for its **quick connection** capability to air compressors thanks to **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup time and **enhancing** overall operational efficiency.

Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or couplings. **Ensuring high-quality** connections promotes both **cost** and

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.1 N**
Air Consumption (at 6 bar inlet)	**200 l/m / 7 scfm**
Noise Level (at 6 bar inlet)	**83 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**10 Bar / 145 psi**
Nozzle length	**19 mm / 0.70”**

MATERIALS

Handle	**Acetal**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Acetal**
Nozzle	**Rubber**

VERSIONS

Code	Description	Connection
STD TP 1002EU74	Airset Standard Tip EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.