Standard blow gun with safety nozzle and air plug



AIRSET STANDARD

Code: STD S3 1002E74

Standard L130 S blow gun with pre-mounted **European profile DN 7.4 air plug** for quick connection. Equipped with a **slotted rubber nozzle** that generates a **wide and effective jet**. The nozzle is silenced for **noise reduction**, and the **rubber tip** has been specially designed for **sensitive applications** where the blown surface must not be damaged.

Features

- **Ergonomic**: The shape of the blow gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Each Airset Standard blow gun is **individually tested**: no air leaks!
- Hanging options: The gun can be **hung in two ways**: resting on the trigger lever or using the **dedicated hanging support**. Both supports are reinforced for added durability.
- Proven reliability: This blow gun has been used by professionals for **over 30 years**—a trusted and reliable product!

Speed

The Standard blow gun with quick air plug stands out for its ability to **quickly connect** to air compressors using specially designed plugs. This system allows operators to **easily connect and disconnect** the tool, reducing setup time and **optimizing overall efficiency**.

Safety

When working with compressed air, it’s crucial to ensure a **perfect connection** to avoid leaks, which often occur at fittings or plugs. **Ensuring high-quality connections** helps save both **money and energy**. Standard blow guns with air plugs provide **long-lasting sealing** and **consistent connection quality**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.3 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.7 scfm**
Noise Level (at 6 bar inlet)	**80 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**10 Bar / 145 psi**
Nozzle length	**137 mm / 5.40”**

MATERIALS

Handle	**Acetal**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Acetal**
Pipe	**Stainless steel**
Nozzle	**Rubber**

VERSIONS

Code	Description	Connection
STD S3 1002EU74	Airset Standard L130 S EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.