

# Standard blow gun with safety nozzle and air plug



## AIRSET STANDARD

**Code: STD S3 1002E74**

Standard L130 S blow gun with pre-mounted **European profile DN 7.4 air plug** for quick connection. Equipped with a **slotted rubber nozzle** that generates a **wide and effective jet**. The nozzle is silenced for **noise reduction**, and the **rubber tip** has been specially designed for **sensitive applications** where the blown surface must not be damaged.

## Features

- **Ergonomic:** The shape of the blow gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Each Airset Standard blow gun is **individually tested**: no air leaks!
- Hanging options: The gun can be **hung in two ways**: resting on the trigger lever or using the **dedicated hanging support**. Both supports are reinforced for added durability.
- Proven reliability: This blow gun has been used by professionals for **over 30 years**—a trusted and reliable product!

## Speed

The Standard blow gun with quick air plug stands out for its ability to **quickly connect** to air compressors using specially designed plugs. This system allows operators to **easily connect and disconnect** the tool, reducing setup time and **optimizing overall efficiency**.

## Safety

When working with compressed air, it's crucial to ensure a **perfect connection** to avoid leaks, which often occur at fittings or plugs. **Ensuring high-quality connections** helps save both **money and energy**. Standard blow guns with air plugs provide **long-lasting sealing** and **consistent connection quality**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.3 N</b>
Air Consumption (at 6 bar inlet)	<b>275 l/m / 9.7 scfm</b>
Noise Level (at 6 bar inlet)	<b>80 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>10 Bar / 145 psi</b>
Nozzle length	<b>137 mm / 5.40"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Acetal</b>
Pipe	<b>Stainless steel</b>
Nozzle	<b>Rubber</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD S3 1002EU74	Airset Standard L130 S EU	European Profile DN 7.4

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA</b> Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.