

Standard blow gun with safety pipe and air plug



AIRSET STANDARD

Code: STD H3 1002E74

Standard L130 Osha Blow Gun, with a quick connection already mounted, **European profile DN 7.4** for connection to **quick couplings**. Special tube with a **security vent**: in case of obstruction in the exit hole, air escapes through the side windows. **Compliant with OSHA standards**. The gun is equipped with a bent stainless steel nozzle, **suitable for tough environments and extreme conditions**.

Features

- **Ergonomic**: The design of the gun minimizes **repetitive use injuries**. Suitable for both large and small hands.
- Airset Standard guns are **individually tested**: no air leaks!
- Can be hung: The gun can be **attached** in two ways: either supported on the trigger lever or hung on a **dedicated support**. Both supports are reinforced for greater durability.
- Historic product: This gun has been in use for **30 years**, trusted by professionals: a tested and reliable product!

Speed

The Standard blow gun with air plug is distinguished by its ability to **quickly connect** to air compressors through **specially designed connections**. This system allows operators to easily connect and disconnect the gun, reducing setup times and **optimizing** overall operational efficiency.

Safety

When using compressed air, it is crucial to ensure the **connection is perfect** to avoid leaks, which often occur in fittings or couplings. **Ensuring optimal connection quality** not only promotes **economic savings** but also **energy efficiency**. The Standard blow guns with air plugs **ensure a durable seal** and consistent **quality** of your **connection**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.5 N
Air Consumption (at 6 bar inlet)	275 l/m / 9.7 scfm
Noise Level (at 6 bar inlet)	83 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	10 Bar / 145 psi
Nozzle length	123 mm / 5"

MATERIALS

Handle	Acetal
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Acetal
Nozzle	Stainless steel

VERSIONS

Code	Description	Connection
STD H3 1002EU74	Airset Standard L130 Osha EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.