

# Standard blow gun with safety pipe and air plug



AIRSET STANDARD

**Code: STD H3 1002E74**

Standard L130 Osha Blow Gun, with a quick connection already mounted, **European profile DN 7.4** for connection to **quick couplings**. Special tube with a **security vent**: in case of obstruction in the exit hole, air escapes through the side windows. **Compliant with OSHA standards**. The gun is equipped with a bent stainless steel nozzle, **suitable for tough environments and extreme conditions**.

## Features

- **Ergonomic**: The design of the gun minimizes **repetitive use injuries**. Suitable for both large and small hands.
- Airset Standard guns are **individually tested**: no air leaks!
- Can be hung: The gun can be **attached** in two ways: either supported on the trigger lever or hung on a **dedicated support**. Both supports are reinforced for greater durability.
- Historic product: This gun has been in use for **30 years**, trusted by professionals: a tested and reliable product!

## Speed

The Standard blow gun with air plug is distinguished by its ability to **quickly connect** to air compressors through **specially designed connections**. This system allows operators to easily connect and disconnect the gun, reducing setup times and **optimizing** overall operational efficiency.

## Safety

When using compressed air, it is crucial to ensure the **connection is perfect** to avoid leaks, which often occur in fittings or couplings. **Ensuring optimal connection quality** not only promotes **economic savings** but also **energy efficiency**. The Standard blow guns with air plugs **ensure a durable seal** and consistent **quality of your connection**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.5 N</b>
Air Consumption (at 6 bar inlet)	<b>275 l/m / 9.7 scfm</b>
Noise Level (at 6 bar inlet)	<b>83 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>10 Bar / 145 psi</b>
Nozzle length	<b>123 mm / 5"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Acetal</b>
Nozzle	<b>Stainless steel</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD H3 1002EU74	Airset Standard L130 Osha EU	European Profile DN 7.4

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA</b> Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.