Standard blow gun with safety pipe and air plug



AIRSET STANDARD

Code: STD H3 1002E74

Standard L130 Osha Blow Gun, with a quick connection already mounted, **European profile DN 7.4** for connection to **quick couplings**. Special tube with a **security vent**: in case of obstruction in the exit hole, air escapes through the side windows. **Compliant with OSHA standards**. The gun is equipped with a bent stainless steel nozzle, **suitable for tough environments and extreme conditions.**

Features

- **Ergonomic**: The design of the gun minimizes **repetitive use injuries**. Suitable for both large and small hands.
- Airset Standard guns are **individually tested**: no air leaks!
- Can be hung: The gun can be **attached** in two ways: either supported on the trigger lever or hung on a **dedicated support**. Both supports are reinforced for greater durability.
- Historic product: This gun has been in use for **30 years**, trusted by professionals: a tested and reliable product!

Speed

The Standard blow gun with air plug is distinguished by its ability to **quickly connect** to air compressors through **specially designed connections**. This system allows operators to easily connect and disconnect the gun, reducing setup times and **optimizing** overall operational efficiency.

Safety

When using compressed air, it is crucial to ensure the **connection is perfect** to avoid leaks, which often occur in fittings or couplings. **Ensuring optimal connection quality** not only promotes **economic savings** but also **energy efficiency**. The Standard blow guns with air plugs **ensure a durable seal** and consistent **quality** of your **connection**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.5 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.7 scfm**
Noise Level (at 6 bar inlet)	**83 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**10 Bar / 145 psi**
Nozzle length	**123 mm / 5”**

MATERIALS

Handle	**Acetal**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Acetal**
Nozzle	**Stainless steel**

VERSIONS

Code	Description	Connection
STD H3 1002EU74	Airset Standard L130 Osha EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.