

# Standard blow gun with silenced nozzle and air plug



AIRSET STANDARD

**Code: STD SL 1002E74**

Standard Silent Blow Gun with a pre-assembled **quick air plug**, **European profile DN 7.4**, for **quick connection**. Equipped with a **quiet safety nozzle**. The **soft rubber tip** prevents damage to delicate surfaces. Ideal in situations where a **compact blow gun** is preferred over a long nozzle. The gun delivers a **broad and powerful jet**, ideal for all **cleaning and drying operations**.

## Features

- **Ergonomic:** The shape of the gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: zero air leaks guaranteed!
- **Hangable:** The gun can be **hung** in two ways—resting on the trigger lever or on the **dedicated hook**. Both supports are reinforced for greater wear resistance.
- **Proven product:** This gun has been around for **30 years**, used by professionals: a tested and reliable product!

## Speed

The Standard Blow Gun with quick air plug stands out for its ability to **quickly connect** to air compressors, thanks to the **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup times and **maximizing** operational efficiency.

## Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or plugs. Ensuring **optimal connection quality** not only promotes **economic** but also **energy savings**. Standard blow guns with quick air plugs **guarantee durable sealing** and **consistent connection quality**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.3 N</b>
Air Consumption (at 6 bar inlet)	<b>275 l/m / 9.7 scfm</b>
Noise Level (at 6 bar inlet)	<b>80 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>10 Bar / 145 psi</b>
Nozzle length	<b>19 mm / 0.70"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Acetal</b>
Nozzle	<b>Aluminum and Rubber</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD SL 1002EU74	Airset Standard Silenced EU	European Profile DN 7.4

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA</b> Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.