Standard blow gun with silenced nozzle and air plug



AIRSET STANDARD

Code: STD SL 1002E74

Standard Silent Blow Gun with a pre-assembled **quick air plug**, **European profile DN 7.4**, for **quick connection**. Equipped with a **quiet safety nozzle**. The **soft rubber tip** prevents damage to delicate surfaces. Ideal in situations where a **compact blow gun** is preferred over a long nozzle. The gun delivers a **broad and powerful jet**, ideal for all **cleaning and drying operations**.

Features

- **Ergonomic**: The shape of the gun minimizes the risk of **repetitive strain injuries**. Suitable for both large and small hands.
- Airset Standard blow guns are **individually tested**: zero air leaks guaranteed!
- **Hangable**: The gun can be **hung** in two ways—resting on the trigger lever or on the **dedicated hook**. Both supports are reinforced for greater wear resistance.
- **Proven product**: This gun has been around for **30 years**, used by professionals: a tested and reliable product!

Speed

The Standard Blow Gun with quick air plug stands out for its ability to **quickly connect** to air compressors, thanks to the **specially designed couplings**. This system allows operators to connect and disconnect the gun with **ease**, reducing setup times and **maximizing** operational efficiency.

Safety

When using compressed air, it is essential to ensure a **perfect connection** to avoid leaks, which often occur at fittings or plugs. Ensuring **optimal connection quality** not only promotes **economic** but also **energy savings**. Standard blow guns with quick air plugs **guarantee durable sealing** and **consistent connection quality**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.3 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.7 scfm**
Noise Level (at 6 bar inlet)	**80 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**10 Bar / 145 psi**
Nozzle length	**19 mm / 0.70”**

MATERIALS

Handle	**Acetal**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Acetal**
Nozzle	**Aluminum and Rubber**

VERSIONS

Code	Description	Connection
STD SL 1002EU74	Airset Standard Silenced EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.