# Tucano blow gun with flat nozzle and air plug

AIRSET® TUCANO

**Cod. TCN PF 4040E74**

Tucano Blow Flat blow gun, with a pre-mounted air plug, **European profile DN 7.4**, for connection to a **quick coupling**. Equipped with a **flat nozzle** for a **wide** and **powerful blow**, but with **low noise level**. Useful in applications where you need to blow away large quantities of chips, debris, or quickly dry **large surfaces**

## Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **fast connection** to air compressors via specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

## Safety

When using compressed air, leaks occur most frequently at fittings or plugs. It is therefore essential to ensure the **quality** of the connection is perfect; this guarantees both **cost and energy savings**. Tucano blow guns with air plug can ensure a durable seal and high-quality connection.

## Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing Force (at 6 bar inlet) | **2.5 N** |
| Air Consumption (at 6 bar inlet) | **275 l/m / 9.5 scfm** |
| Noise Level (at 6 bar inlet) | **80 dB(A)** |
| Connection | **European Profile DN 7.4** |
| Weight | **136 g / 0.30 lbs** |
| Working temperature | **-10°C/70°C / 14/158 °F** |
| Max. Pressure | **16 Bar / 235 psi** |
| Nozzle length | **56 mm / 2”** |

MATERIALS

| | |
|---|---|
| Handle | **Nylon and Rubber** |
| Thread | **Brass** |
| Air Plug | **Steel with Anti-Corrosion Treatment** |
| Valve | **Acetal and Stainless Steel** |
| Body | **Nylon** |
| Nozzle | **Nylon** |

VERSIONS

| Code | Description | Connection |
|---|---|---|
| TCN PF 4040EU74 | Airset Tucano Blow Flat EU | European Profile DN 7.4 |

REGULATIONS

| |
|---|
| **EU 2003/10/CE** Max. 85 dB |
| **OSHA** Conforme alle normative OSHA |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.