# TUCANO L130S - BLOW GUN AND SPIRAL HOSE KIT

AIRSET® TUCANO

**Cod. KPPN S340 56**

Airset Tucano L130S professional blow gun, with safety nozzle, equipped with spiral hose. Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

**Spiral hose features**

- Made of polyurethane 95 shore
- Swiveling fittings, male 1/4"
- **Fittings equipped with o-rings**: no need to put teflon on fittings, ready to use with no air leaks!
- Fitted with plastic spring guard: scratchproof, especially on delicate surfaces

**Available in different diameter and length**
**Blow gun features**

- Ergonomic grip
- Designed for professional industrial use
- Made of durable materials. Metal parts made of stainless steel, corrosion resistant
- Ergonomic handle: made of soft rubber. Variable airflow trigger for a reduced noise level and increased efficiency
- Solid Brass connection ¼": no air leaks!
- Impact resistant body
- With safety nozzle: Nozzle is silenced for a low noise level. Also, Its rubber tip is designed for delicate surfaces or parts

**Kit can be customized to fit customer needs**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

HOSE MATERIALS

| | |
|---|---|
| Hose | **Polyurethane (PU)** |
| Spring | **Plastic** |
| Fittings | **Brass** |
| O-rings | **Nbr** |

BLOW GUN MATERIALS

| | |
|---|---|
| Handle | **Nylon and rubber** |
| Thread | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Nylon** |
| Pipe | **Stainless steel** |
| Nozzle | **Rubber** |

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,5 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **83 dB(A)** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **10 Bar - 145 psi** |

VERSIONS

| Code | Description | Colour | Connection | øHose | Hose length |
|---|---|---|---|---|---|
| KPPN S34056 | KIT TUCANO L130 PU 5X8 - 4 m | Black | Male 1/4" BSP | 5x8 mm | 4 m - 13 ft |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.