

# TUCANO BLOW GUN PRESSURE REDUCER WITH SAFETY NOZZLE



AIRSET® PRESSURE REDUCER

## Cod. RTE S340 40

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces.

### Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

### Variable airflow trigger

Tucano adopts a special valve which allows a **progressive control of the lever: this reduces the noise level and air consumption.** In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force.

### Ergonomic handle

Tucano offers a Soft-Touch handle, **made of soft ergonomic rubber, for comfort and easy handling.** This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing force (with a 6bar - 90psi inlet)	<b>1 N</b>
Air consumption (with a 6bar - 90psi inlet)	<b>170 l/m - 6 scfm</b>
Sound level (with a 6bar - 90psi inlet)	<b>75 dB(A)</b>
Connection	<b>1/4" BSP</b>
Weight	<b>136 g - 0,30 lbs</b>
Working temperature	<b>-10°/70°</b>
Max. Pressure	<b>6 Bar - 90 psi</b>
Nozzle length	<b>152 mm - 6"</b>

**MATERIALS**

Handle	<b>Nylon and rubber</b>
Connection	<b>Brass</b>
Valve	<b>Acetal and stainless steel</b>
Body	<b>Nylon</b>
Nozzle	<b>Rubber</b>
Pipe	<b>Stainless steel</b>

**VERSIONS**

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RTE S340 40	Tucano Pressure Reducer 130 S	1/4" BSP	3,5	1 N	170 l/m - 6 scfm	75 dB(A)
RTA S340 41	Tucano Pressure Reducer 130 S USA	1/4" NPT	2	0,7 N	80 l/m - 2,83 scfm	60 dB(A)

**REGULATIONS**

**OSHA 1910.95 (b)** Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

<b>OSHA STD 1-13.1</b> Max. 2 bar / 30 psi if the tip becomes blocked
<b>EU 2003/10/CE</b> Max. 85 dB
<b>SUVA PRO</b>

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.