TUCANO BLOW GUN PRESSURE REDUCER WITH SAFETY NOZZLE



Cod. RTE S340 40

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces.

Why use a pressure reduced blow gun?

- Noise reduction: **Air flow is very quiet.**
- Energy saving: **Built in pressure reducer from 6 bar, to 3.5 bar (or 6 bar to 2 bar), allows to consume less air.**
- Safety: blow guns meet European and OSHA regulation; Suva Pro certification as well.

Variable airflow trigger

Tucano adopts a special valve which allows a **progressive control of the lever: this reduces the noise level and air consumption**. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force.

Ergonomic handle

Tucano offers a Soft-Touch handle, **made of soft ergonomic rubber, for comfort and easy handling**. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	**1 N**
Air consumption (with a 6bar - 90psi inlet)	**170 l/m - 6 scfm**
Sound level (with a 6bar - 90psi inlet)	**75 dB(A)**
Connection	**1/4" BSP**
Weight	**136 g - 0,30 lbs**
Working temperature	**-10°/70°**
Max. Pressure	**6 Bar - 90 psi**
Nozzle length	**152 mm - 6"**

MATERIALS

Handle	**Nylon and rubber**
Connection	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Nozzle	**Rubber**
Pipe	**Stainless steel**

VERSIONS

Code	Description	Connection	Output pressure (with 6 bar / 90 psi inlet)	Blowing force (with 6 bar / 90 psi inlet)	Air consumption (with 6 bar / 90 psi inlet)	Sound level (with 6 bar / 90 psi inlet)
RTE S34040	Tucano Pressure Reducer 130 S	1/4" BSP	3,5	1 N	170 l/m - 6 scfm	75 dB(A)
RTA S34041	Tucano Pressure Reducer 130 S USA	1/4" NPT	2	0,7 N	80 l/m - 2,83 scfm	60 dB(A)

REGULATIONS

OSHA 1910.95 (b) Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

OSHA STD 1-13.1 Max. 2 bar / 30 psi if the tip becomes blocked
EU 2003/10/CE Max. 85 dB
SUVA PRO

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.