

Tucano blow gun with angled metal pipe and air plug



AIRSET™ TUCANO

Cod. TCN 30 4040E74

Tucano L130 Blow Gun, with an **air plug** already mounted, **European Profile DN 7.4**, for connection to a **quick-release coupling**. Equipped with a bent **stainless steel** nozzle, suitable for tough environments and extreme conditions.

Speed

The distinctive feature of the Tucano blow gun with an air plug is its ability to **quickly connect** to air compressors through specially designed couplings. This air plug allows operators to **easily connect and disconnect the gun**, reducing setup times and improving overall **efficiency** of operations.

Safety

When using compressed air, leaks occur most frequently at a fitting or coupling. Therefore, it is crucial to ensure that the **quality** of the connection is perfect; this ensures **economic and energy savings**. Tucano blow guns with air plugs can guarantee a high quality and long-lasting seal for your connection.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with an air plug; with a soft-touch rubber handle, designed to maximize the operator's **comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plugs represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.5 N
Air Consumption (at 6 bar inlet)	275 l/m / 9.7 scfm
Noise Level (at 6 bar inlet)	83 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	16 Bar / 235 psi
Nozzle length	123 mm / 5"

MATERIALS

Handle	Nylon and Rubber
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Nylon
Nozzle	Stainless Steel

VERSIONS

Code	Description	Connection
TCN 30 4040EU74	Airset Tucano L130 EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.