

Tucano blow gun with bendable pipe and air plug



AIRSET™ TUCANO

Cod. TCN F3 4040E74

Tucano blow gun with flexible pipe, equipped with a pre-mounted **European profile DN 7.4 air plug**, for connection to a **quick coupling**. The tube, once **bent, holds its shape** and can be positioned as needed. Ideal for **blowing** into **hard-to-reach** or **tight areas** where the user cannot easily access.

Two available lengths:

TCN F3 4040E74 – 327 mm

TCN F2 4040E74 – 497 mm

Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **quick connection** to air compressors through specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

Safety

When using compressed air, leaks most often occur at the fitting or plug. It is therefore essential to ensure **high connection quality**; this guarantees both **cost and energy savings**. Tucano blow guns with air plug ensure long-lasting tightness and connection reliability.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.1 N
Air Consumption (at 6 bar inlet)	190 l/m / 6.7 scfm
Noise Level (at 6 bar inlet)	83 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	16 Bar / 235 psi
Nozzle length	327 mm / 13"

MATERIALS

Handle	Nylon and Rubber
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Nylon
Pipe	PU and Stainless Steel

VERSIONS

Code	Description	Connection	Pipe lenght
TCN F3 4040EU74	Airset Tucano F350 EU	European Profile DN 7.4	327 mm - 13"
TCN F2 4040EU74	Airset Tucano F520 EU	European Profile DN 7.4	497 mm - 20"

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.