Tucano blow gun with bendable pipe and air plug



AIRSET® TUCANO

Cod. TCN F3 4040E74

Tucano blow gun with flexible pipe, equipped with a pre-mounted **European profile DN 7.4 air plug**, for connection to a **quick coupling**. The tube, once **bent**, **holds its shape** and can be positioned as needed. Ideal for **blowing** into **hard-to-reach** or **tight areas** where the user cannot easily access.

Two available lengths:

TCN F3 4040E74 – 327 mm

TCN F2 4040E74 – 497 mm

Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **quick connection** to air compressors through specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

Safety

When using compressed air, leaks most often occur at the fitting or plug. It is therefore essential to ensure **high connection quality**; this guarantees both **cost and energy savings**. Tucano blow guns with air plug ensure long-lasting tightness and connection reliability.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.1 N**
Air Consumption (at 6 bar inlet)	**190 l/m / 6.7 scfm**
Noise Level (at 6 bar inlet)	**83 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**16 Bar / 235 psi**
Nozzle length	**327 mm / 13”**

MATERIALS

Handle	**Nylon and Rubber**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Nylon**
Pipe	**PU and Stainless Steel**

VERSIONS

Code	Description	Connection	Pipe lenght
TCN F3 4040EU74	Airset Tucano F350 EU	European Profile DN 7.4	327 mm - 13"
TCN F2 4040EU74	Airset Tucano F520 EU	European Profile DN 7.4	497 mm - 20"

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.