TUCANO BLOW GUN WITH BENDABLE PIPE

AIRSET® TUCANO

Cod. TCN F3 4040

Safety blow gun with bendable pipe that can be adjusted to the desired position. Once bended it keeps the desired position and can be infinitely adjusted. Perfect for applications that are hard to reach with conventional blow guns. Offers also a better and safety distance from blown surfaces. Pipe construction guarantees resistance to wear.

Variable airflow trigger

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

Ergonomic handle

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Available in 2 lengths:

TCN F3 4040 - 327 mm / 13"

TCN F5 4040 - 497 mm / 20"

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	**2,1 N**
Air consumption (with a 6bar - 90psi inlet)	**190 l/m - 6.7 scfm**
Sound level (with a 6bar - 90psi inlet)	**83 dB(A)**
Connection	**1/4" BSP**
Weight	**136 g - 0.30 lbs**
Working temperature	**-10°/70° - 14/158 °F**
Max. Pressure	**16 Bar - 235 psi**
Nozzle length	**327 mm - 13"**

MATERIALS

Handle	**Nylon and rubber**
Connection	**Brass**
Valve	**Acetal and stainless steel**
Body	**Nylon**
Pipe	**PU and stainless steel**

VERSIONS

Code	Description	Connection	Pipe length
TCN F3 4040	Airset Tucano F350 BSP	1/4" BSP	327 mm - 13"
TCN F3 4041	Airset Tucano F350 NPT	1/4" NPT	327 mm - 13"
TCN F5 4040	Airset Tucano F520 BSP	1/4" BSP	497 mm - 20"
TCN F5 4041	Airset Tucano F520 NPT	1/4" NPT	497 mm - 20"

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA 1910.95 (b) Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.