

# Tucano blow gun with extended safety pipe and air plug



AIRSET™ TUCANO

**Cod. TCN H5 4040E74**

Tucano blow gun with long safety nozzle, equipped with a pre-mounted **European profile DN 7.4 air plug**, for connection to a **quick coupling**. Features a special tube with safety relief: if the outlet hole is blocked, air escapes through side vents. OSHA compliant.

## Three available lengths:

TCN H5 4040E74 – 327 mm

TCN H2 4040E74 – 497 mm

TCN H0 4040E74 – 1012 mm

## Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **quick connection** to air compressors through specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

## Safety

When using compressed air, leaks most often occur at the fitting or plug. It is therefore essential to ensure **high connection quality**; this guarantees both **cost and energy savings**. Tucano blow guns with air plug ensure long-lasting tightness and connection reliability.

## Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing Force (at 6 bar inlet)	<b>2.3 N</b>
Air Consumption (at 6 bar inlet)	<b>275 l/m / 9.7 scfm</b>
Noise Level (at 6 bar inlet)	<b>80 dB(A)</b>
Connection	<b>European Profile DN 7.4</b>
Weight	<b>136 g / 0.30 lbs</b>
Working temperature	<b>-10°C/70°C / 14/158 °F</b>
Max. Pressure	<b>16 Bar / 235 psi</b>
Nozzle length	<b>327 mm / 13"</b>

**MATERIALS**

Handle	<b>Nylon and Rubber</b>
Thread	<b>Brass</b>
Air Plug	<b>Steel with Anti-Corrosion Treatment</b>
Valve	<b>Acetal and Stainless Steel</b>
Body	<b>Nylon</b>
Nozzle	<b>Stainless Steel</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>	<b>Pipe lenght</b>
TCN H5 4040EU74	Airset Tucano L350 Osha EU	European Profile DN 7.4	327 mm - 13"
TCN H2 4040EU74	Airset Tucano L520 Osha EU	European Profile DN 7.4	497 mm - 20"
TCN H0 4040EU74	Airset Tucano L1000 Osha EU	European Profile DN 7.4	1012 mm - 40"

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA</b> Compliant to osha regulation

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.