

# Tucano blow gun with safety nozzle and air plug



AIRSET® TUCANO

Cod. TCN S3 4040E74

Tucano L130 S Blow Gun, with a pre-installed **European profile DN 7.4** quick plug for connection to a **quick-release coupling**. Equipped with a **rubber slotted nozzle** that generates a **wide and effective air jet**. The nozzle is **silenced** for **noise reduction**.

## Speed

The standout feature of the Tucano blow gun with quick coupling is its ability to **connect quickly** to air compressors using specially designed fittings. This coupling allows operators to **easily connect and disconnect the blow gun**, reducing setup times and improving **overall efficiency**.

## Safety

When using compressed air, leaks most often occur at fittings or couplings. It is therefore essential to ensure the **quality** of the connection; this guarantees **cost savings and energy efficiency**. Tucano blow guns with quick coupling ensure a high-quality and long-lasting seal.

## Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with quick coupling; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Quick-coupling blow guns represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                  |                                |
|----------------------------------|--------------------------------|
| Blowing Force (at 6 bar inlet)   | <b>2.3 N</b>                   |
| Air Consumption (at 6 bar inlet) | <b>275 l/m / 9.7 scfm</b>      |
| Noise Level (at 6 bar inlet)     | <b>80 dB(A)</b>                |
| Connection                       | <b>European Profile DN 7.4</b> |
| Weight                           | <b>136 g / 0.30 lbs</b>        |
| Working temperature              | <b>-10°C/70°C / 14/158 °F</b>  |
| Max. Pressure                    | <b>16 Bar / 235 psi</b>        |
| Nozzle length                    | <b>162 mm - 6"</b>             |

## MATERIALS

|          |                                            |
|----------|--------------------------------------------|
| Handle   | <b>Nylon and Rubber</b>                    |
| Thread   | <b>Brass</b>                               |
| Air Plug | <b>Steel with Anti-Corrosion Treatment</b> |
| Valve    | <b>Acetal and Stainless Steel</b>          |
| Body     | <b>Nylon</b>                               |
| Nozzle   | <b>Rubber</b>                              |
| Pipe     | <b>Stainless steel</b>                     |

## VERSIONS

| Code            | Description             | Connection              |
|-----------------|-------------------------|-------------------------|
| TCN S3 4040EU74 | Airset Tucano L130 S EU | European Profile DN 7.4 |

## REGULATIONS

|                                          |
|------------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB          |
| <b>OSHA</b> Compliant to osha regulation |
| <b>SUVA PRO</b>                          |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.