Tucano blow gun with safety pipe and air plug



AIRSET® TUCANO

Cod. TCN H3 4040E74

Tucano L130 Osha blow gun, with a pre-mounted **European profile DN 7.4 air plug**, for connection to a **quick coupling** Equipped with a special tube featuring a **safety relief**: in case the outlet hole is blocked, air escapes through the **side vents**. **OSHA compliant**

Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **quick connection** to air compressors via specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

Safety

When using compressed air, leaks most often occur at the fitting or plug. It is therefore essential to ensure **high connection quality**; this guarantees both **cost and energy savings**. Tucano blow guns with air plug ensure long-lasting tightness and connection reliability.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; it features a soft-touch rubber grip designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.3 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.7 scfm**
Noise Level (at 6 bar inlet)	**80 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**16 Bar / 235 psi**
Nozzle length	**123 mm / 5”**

MATERIALS

Handle	**Nylon and Rubber**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Nylon**
Nozzle	**Stainless Steel**

VERSIONS

Code	Description	Connection
TCN H3 4040EU74	Airset Tucano L130 Osha EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Conforme alle normative OSHA

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.