

## ECO BLOW GUN WITH SHORT NOZZLE



**AIRSET<sup>®</sup> ECO**

HIGH BLOWING FORCE

### **Cod. ECO UG 1000**

With short metal nozzle. Useful when a compact blow gun is preferable to a larger one. The nozzle creates a concentrated jet of air which reduces turbulence, enabling a more precise, effective blowing force. Nozzle construction guarantees resistance to wear.

### **Two hanging options**

By the trigger or by the specially designed holder. Both surrounding areas are enforced to withstand increased wear

### **Ergonomic**

Airset ECO blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

### **Airset ECO blow guns are tested individually during production: no leaks!**

Built in ¼" female plastic thread

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Blowing force (with a 6bar - 90psi inlet)   | <b>2,1 N</b>                |
| Air consumption (with a 6bar - 90psi inlet) | <b>200 l/m - 7 scfm</b>     |
| Sound level (with a 6bar - 90psi inlet)     | <b>83 dB(A)</b>             |
| Connection                                  | <b>1/4" BSP</b>             |
| Weight                                      | <b>136 g - 0.30 lbs</b>     |
| Working temperature                         | <b>-10°/70° - 14/158 °F</b> |
| Max. Pressure                               | <b>10 Bar - 145 psi</b>     |
| Nozzle length                               | <b>19mm - 0.70"</b>         |

## MATERIALS

|        |                                   |
|--------|-----------------------------------|
| Handle | <b>Acetal</b>                     |
| Thread | <b>Acetal</b>                     |
| Valve  | <b>Acetal and stainless steel</b> |
| Body   | <b>Acetal</b>                     |
| Nozzle | <b>Aluminum</b>                   |

## VERSIONS

| Code        | Description          | Connection |
|-------------|----------------------|------------|
| ECO UG 1000 | Airset ECO Metal BSP | 1/4" BSP   |

## REGULATIONS

|                                       |
|---------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB       |
| <b>OSHA 1910.95 (b)</b> Max. 90 dB 8h |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.