

## STANDARD BLOW GUN WITH RUBBER TIP



AIRSET<sup>®</sup> STANDARD

### **Cod. STD TP 1002**

Nozzle made of scratchproof rubber to minimize the risk on delicate surfaces. Rubber tip also works as a pressurizer when cleaning pipes or molds, for a more efficient cleaning. Useful when a compact blow gun is preferable to a larger one.

### **Historic Product**

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

### **Two hanging options**

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

### **Ergonomic**

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

### **Airset Standard blow guns are tested individually during production: no leaks!**

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing force (with a 6bar - 90psi inlet)	<b>2,1 N</b>
Air consumption (with a 6bar - 90psi inlet)	<b>200 l/m - 7 scfm</b>
Sound level (with a 6bar - 90psi inlet)	<b>83 dB(A)</b>
Connection	<b>1/4" BSP</b>
Weight	<b>136 g - 0.30 lbs</b>
Working temperature	<b>-10°/70° - 14/158 °F</b>
Max. Pressure	<b>10 Bar - 145 psi</b>
Nozzle length	<b>19 mm - 0.70"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Valve	<b>Acetal and stainless steel</b>
Body	<b>Acetal</b>
Nozzle	<b>Rubber</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD TP 1002	Airset Standard Tip BSP	1/4" BSP
STD TP 1003	Airset Standard Tip NPT	1/4" NPT

**REGULATIONS**

<b>EU 2003/10/CE</b> Max. 85 dB
<b>OSHA 1910.95 (b)</b> Max. 90 dB 8h

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.