

# Tucano blow gun with plastic nozzle and air plug



AIRSET® TUCANO

Cod. TCN PL 4040E74

Tucano Blow Gun with an **air plug** already mounted, **European Profile DN 7.4**, for connection to a **quick-release coupling**. The nozzle creates a concentrated airflow, minimizes turbulence, and provides precise and effective blowing. The nozzle is made of durable, wear-resistant plastic; additionally, the plastic material is scratch-resistant for more sensitive surfaces.

## Speed

The distinctive feature of the Tucano blow gun with an air plug is its ability to **quickly connect** to air compressors through specially designed couplings. This coupling allows operators to **easily connect and disconnect the gun**, reducing setup times and improving overall **efficiency** of operations.

## Safety

When using compressed air, leaks occur more frequently at a fitting or coupling. Therefore, it is crucial to ensure that the **quality** of the connection is perfect; this guarantees **economic and energy savings**. Tucano blow guns with quick couplings can ensure a high-quality and long-lasting seal for your connection.

## Ergonomics

**Ergonomics** is another crucial aspect of the Tucano blow gun with air plug with a soft-touch rubber handle designed to maximize the **comfort** of the operator during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plugs represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                  |                                |
|----------------------------------|--------------------------------|
| Blowing Force (at 6 bar inlet)   | <b>2.1 N</b>                   |
| Air Consumption (at 6 bar inlet) | <b>200 l/m / 7 scfm</b>        |
| Noise Level (at 6 bar inlet)     | <b>83 dB(A)</b>                |
| Connection                       | <b>European Profile DN 7.4</b> |
| Weight                           | <b>136 g / 0.30 lbs</b>        |
| Working temperature              | <b>-10°C/70°C / 14/158 °F</b>  |
| Max. Pressure                    | <b>16 Bar / 235 psi</b>        |
| Nozzle length                    | <b>123 mm / 5"</b>             |

## MATERIALS

|          |                                            |
|----------|--------------------------------------------|
| Handle   | <b>Nylon and Rubber</b>                    |
| Thread   | <b>Brass</b>                               |
| Air Plug | <b>Steel with Anti-Corrosion Treatment</b> |
| Valve    | <b>Acetal and Stainless Steel</b>          |
| Body     | <b>Nylon</b>                               |
| Nozzle   | <b>Nylon</b>                               |

## VERSIONS

| Code            | Description           | Connection              |
|-----------------|-----------------------|-------------------------|
| TCN PL 4040EU74 | Airset Tucano Blow EU | European Profile DN 7.4 |

## REGULATIONS

**EU 2003/10/CE** Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.