

## TUCANO BLOW GUN WITH SAFETY PIPE



AIRSET® TUCANO

### **Cod. TCN H3 4040**

Special pipe with side ventilation: prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1). Also, blow gun adopts an angled stainless steel nozzle, designed for professional industrial use. Nozzle construction guarantees resistance to wear; at the same time, stainless steel is resistant to corrosion and chemicals.

### **Variable airflow trigger**

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

### **Ergonomic handle**

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Blowing force (with a 6bar - 90psi inlet)   | <b>2,3 N</b>                |
| Air consumption (with a 6bar - 90psi inlet) | <b>275 l/m - 9.7 scfm</b>   |
| Sound level (with a 6bar - 90psi inlet)     | <b>80 dB(A)</b>             |
| Connection                                  | <b>1/4" BSP</b>             |
| Weight                                      | <b>136 g - 0.30 lbs</b>     |
| Working temperature                         | <b>-10°/70° - 14/158 °F</b> |
| Max. Pressure                               | <b>16 Bar - 235 psi</b>     |
| Nozzle length                               | <b>123 mm - 5"</b>          |

## MATERIALS

|            |                                   |
|------------|-----------------------------------|
| Handle     | <b>Nylon and rubber</b>           |
| Connection | <b>Brass</b>                      |
| Valve      | <b>Acetal and stainless steel</b> |
| Body       | <b>Nylon</b>                      |
| Nozzle     | <b>Stainless steel</b>            |

## VERSIONS

| Code        | Description                 | Connection |
|-------------|-----------------------------|------------|
| TCN H3 4040 | Airset Tucano L130 Osha BSP | 1/4" BSP   |
| TCN H3 4041 | Airset Tucano L130 Osha NPT | 1/4" NPT   |

## REGULATIONS

|                                                                       |
|-----------------------------------------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB                                       |
| <b>OSHA 1910.95 (b)</b> Max. 90 dB 8h                                 |
| <b>OSHA STD 1-13.1</b> Max. 2 bar / 30 psi if the tip becomes blocked |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.