Tucano blow gun with flat nozzle and air plug



AIRSET® TUCANO

Cod. TCN PF 4040E74

Tucano Blow Flat blow gun, with a pre-mounted air plug, **European profile DN 7.4**, for connection to a **quick coupling**. Equipped with a **flat nozzle** for a **wide** and **powerful blow**, but with **low noise level**. Useful in applications where you need to blow away large quantities of chips, debris, or quickly dry **large surfaces**

Speed

The distinctive feature of the Tucano blow gun with air plug is its ability for **fast connection** to air compressors via specially designed fittings. This plug allows operators to **easily connect and disconnect the gun**, reducing setup time and improving overall **operational efficiency**.

Safety

When using compressed air, leaks occur most frequently at fittings or plugs. It is therefore essential to ensure the **quality** of the connection is perfect; this guarantees both **cost and energy savings**. Tucano blow guns with air plug can ensure a durable seal and high-quality connection.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug; featuring a soft-touch rubber grip, designed to maximize **operator comfort** during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plug offer an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.5 N**
Air Consumption (at 6 bar inlet)	**275 l/m / 9.5 scfm**
Noise Level (at 6 bar inlet)	**80 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**16 Bar / 235 psi**
Nozzle length	**56 mm / 2”**

MATERIALS

Handle	**Nylon and Rubber**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Nylon**
Nozzle	**Nylon**

VERSIONS

Code	Description	Connection
TCN PF 4040EU74	Airset Tucano Blow Flat EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Conforme alle normative OSHA

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.