# STANDARD BLOW GUN WITH EXTENDED METAL PIPE

AIRSET STANDARD

**Cod. STD 35 1002**

Safety blow gun with an extended pipe for narrow, hard-to-reach spaces. Offers also a better and safety distance from blown surfaces. Pipe is made of stainless steel for professional industrial use. Pipe construction guarantees resistance to a very high mechanical wear; at the same time, stainless steel is resistant to corrosion and chemicals.

**Historic Product**

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

**Two hanging options**

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

**Ergonomic**

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

**Airset Standard blow guns are tested individually during production: no leaks!**

Built in ¼" Female brass thread, for a safe connection with no leaks

**Available in 3 lenghts:**

STD 35 1002 - 327 mm / 13"

STD 52 1002 - 497 mm / 20"

STD 10 1002 - 1012 mm / 40"

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,3 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **83 dB(A)** |
| Connection | **1/4" BSP** |
| Weight | **136 g - 0.30 lbs** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **10 Bar - 145 psi** |
| Nozzle length | **327 mm - 13"** |

MATERIALS

| | |
|---|---|
| Handle | **Acetal** |
| Thread | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Acetal** |
| Nozzle | **Stainless steel** |

VERSIONS

| Code | Description | Connection | Pipe lenght |
|---|---|---|---|
| STD 35 1002 | Airset STD L350 BSP | 1/4" BSP | 327 mm - 13" |
| STD 52 1002 | Airset STD L520 BSP | 1/4" BSP | 497 mm - 20" |
| STD 10 1002 | Airset STD L1000 BSP | 1/4" BSP | 1012 mm - 40" |

REGULATIONS

| | |
|---|---|
| **OSHA 1910.95 (b)** Max. 90 dB 8h | |
| **EU 2003/10/CE** Max. 85 dB | |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.