# STANDARD BLOW GUN WITH SAFETY NOZZLE

AIRSET STANDARD

**Cod. STD S3 1002**

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

**Historic Product**

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

**Two hanging options**

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

**Ergonomic**

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

**Airset Standard blow guns are tested individually during production: no leaks!**

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,3 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **80 dB(A)** |
| Connection | **1/4" BSP** |
| Weight | **136 g - 0.30 lbs** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **10 Bar - 145 psi** |
| Nozzle length | **137 mm - 5.40"** |

MATERIALS

| | |
|---|---|
| Handle | **Acetal** |
| Thread | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Acetal** |
| Pipe | **Stainless steel** |
| Nozzle | **Rubber** |

VERSIONS

| Code | Description | Connection |
|---|---|---|
| STD S3 1002 | Airset Standard L130 S BSP | 1/4" BSP |
| STD S3 1003 | Airset Standard L130 S NPT | 1/4" NPT |

REGULATIONS

| |
|---|
| **OSHA 1910.95 (b)** Max. 90 dB 8h |
| **OSHA STD 1-13.1** Max. 2 bar / 30 psi if the tip becomes blocked |
| **EU 2003/10/CE** Max. 85 dB |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.