# TUCANO BLOW GUN WITH EXTENDED METAL PIPE

AIRSET® TUCANO

**Cod. TCN 35 4040**

Safety blow gun with an extended pipe for narrow, hard-to-reach spaces. Offers also a better and safety distance from blown surfaces. Pipe is made of stainless steel for professional industrial use. Pipe construction guarantees resistance to a very high mechanical wear; at the same time, stainless steel is resistant to corrosion and chemicals.

**Variable airflow trigger**

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

**Ergonomic handle**

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

**Available in 3 lenghts:**

TCN 35 4040 - 327 mm / 13"

TCN 52 4040 - 497 mm / 20"

TCN 10 4040 - 1012 mm / 40"

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,3 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **83 dB(A)** |
| Connection | **1/4" BSP** |
| Weight | **136 g - 0.30 lbs** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **16 Bar - 235 psi** |
| Nozzle length | **327 mm - 13"** |

MATERIALS

| | |
|---|---|
| Handle | **Nylon and rubber** |
| Connection | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Nylon** |
| Pipe | **Stainless steel** |

VERSIONS

| Code | Description | Connection | Pipe lenght |
|---|---|---|---|
| TCN 35 4040 | Airset Tucano L350 BSP | 1/4" BSP | 327 mm - 13" |
| TCN 52 4040 | Airset Tucano L520 BSP | 1/4" BSP | 497 mm - 20" |
| TCN 10 4040 | Airset Tucano L1000 BSP | 1/4" BSP | 1012 mm - 40" |

REGULATIONS

| |
|---|
| **EU 2003/10/CE** Max. 85 dB |
| **OSHA 1910.95 (b)** Max. 90 dB 8h |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.