AP 40L 24V ELECTRIC PUMP WITH ANTI SIPHON VALVE

CARBUSET
POMPE ELETTRICHE AP 40L

Cod. APL 40L2

AP 40L electric pump offers a built-in anti-siphon valve. 3 meters power cables with jumper cables 24 VDC. AP 40L is a centrifugal pump. Suitable for barrel or tank transfer. **Can transfer different liquids such as water, anti-freeze, diesel, motor oil.**

Anti-siphon system

AP 40L adopts a valve which is designed to **prevent siphoning of liquid from an aboveground drum to the delivery hose installed at a lower level.**

Safe

AP 40L pump offers a **motor with double insulated body, this makes the pump robust and durable.** Moreover, **double insulation allows water and emulsion transferring in complete safety.** AP 40L pump has IPX4 (protection against splashing water) and CE marking.

Metal parts are made of stainless steel, for an improved durability and corrosion resistance.

Complete kit

AP 40L pump comes in a **complete kit: ready to use!** Kit is composed of a telescopic suction tube with filter (adjustable from 330 to 970 mm high), delivery hose, manual dispensing nozzle and power cables with 3 meters jumper cables 24 VDC. Pump offers a built-in drum connection with 2" BSP.

Features

- Pump offers a 2” BSP connection
- **Can be easily installed or removed thanks to a quick coupling system**
- Pump can be rotated in 10 different positions
- Side handle works as a cable storage
- Nozzle hanger: keeps hose within reach and off the floor
- **Available with AL 100 digital flow meter**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Code	**APL 40L2**
Voltage	**24 V**
Current type	**DC**
Absorbed power	**135 W**
Absorption	**5,6 A**
Insulation category	**III**
Flow rate	**35 l/m - 9,2 gpm**
Discharge head	**1 m**
Sound level	**70 dB**
Operating temperature	**-10°C + 40°C / 14 °F to 104 °F**

MATERIALS

Pump	**Acetal**
Dispensing nozzle	**Acetal**
Telescopic suction tube	**Polypropylene**
Delivery hose	**Rubber**
Metal parts	**Stainless steel**

EQUIPMENT SUPPLIED

Pump
N° 2 Clamps
Telescopic suction tube with filter
Manual dispensing nozzle
2,5 m (8 ft) Delivery hose
Drum connection 2" BSP
3 meters (10 ft) jumper cables 24 VDC

VERSIONS

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

Code	Description
APL 40L2	Pump AP 40L 24v
APL 40L250	Pump AP 40L 24v + Flow meter AL 100

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.